

ALUMINIUM  
4 1/2"

# CASEMENT

## AWNING



# ALUMINIUM 4 1/2"

## CASEMENT AWNING

### CHARACTERISTICS

1. Multi-chamber welded PVC frame with an extruded aluminium extension, interior and exterior.
2. Triple weather strip PVC welded sash with an extruded aluminium facade.
3. 4 1/2" frame positioning the glass in the warmer part of the wall.
4. Matches other products from SONIPLASTICS and DECKO DOORS.

### OPTIONS

- A. Double or triple glass.
- B. Multitude of interior or exterior mouldings.
- C. Choice of interior and exterior colors.

### PERFORMANCES

CASEMENT	NAFS-11	CSA A440-00
Air infiltration/exfiltration:	A3	A3
Water resistance:	720Pa (100)	B7
Design pressure :	3600Pa (75)	C5
Primary designator :	LC-CP75 800 x 1500 (32 x 59) Type C	

CASEMENT	NAFS-11	CSA A440-00
Air infiltration/exfiltration:	A3	A3
Water resistance:	720Pa (100)	B7
Design pressure :	2880Pa (60)	C5
Primary designator :	CW-CP60 800 X 1500 (32 X 59) Type C	

AWNING	NAFS-11	CSA A440-00
Air Infiltration/exfiltration:	A3	A3
Water resistance:	720Pa (100)	B7
Design pressure :	4320Pa (90)	C5
Primary designator :	CW-CP90 1200 x 800 (47 x 32) Type AP	



COMPATIBLE PRODUCTS



[DECKODOORS.COM](http://DECKODOORS.COM)