

PVC  
4 1/2"

# LARGE

## FIXED



# PVC 4 1/2"

## LARGE FIXED

### CHARACTERISTICS

---

1. Multi-chamber welded PVC frame for better insulation.
2. 4 1/2" frame positioning the glass in the warmer part of the wall.
3. Virgin PVC extruded profiles provide a glossy finish and facilitate cleaning.
4. Matches other products from SONIPLASTICS and DECKO DOORS.

### OPTIONS

---

- A. Double or triple glass.
- B. Multitude of interior or exterior mouldings.

### PERFORMANCES

---

<b>Primary designator:</b>	<b>Class CW - PG75 - 1500 x 1500 mm (59 x 59 in) - Type FW</b>
Positive design pressure (DP):	3600 Pa (75.19 psf)
Negative design pressure (DP):	-3600 Pa (-75.19 psf)
Water penetration resistance test pressure:	720 Pa (15.04 psf)
Canadian air infiltration / exfiltration level:	A3

Results obtained according to standards:  
AAMA/WDMA/CSA 101/I.S.2/A440-11 (NAFS 2011), CSA A440S1-09 & CSA A440S1-17  
AAMA/WDMA/CSA 101/I.S.2/A440-17 (NAFS 2017), CSA A440S1-19



COMPATIBLE PRODUCTS



[DECKODOORS.COM](http://DECKODOORS.COM)