

ALUMINIUM
4 1/2"

LARGE

FIXED



ALUMINIUM 4 1/2"

LARGE FIXED

CHARACTERISTICS

1. Multi-chamber welded PVC frame with an extruded aluminium extension, interior and exterior.
2. 4 1/2" frame positioning the glass in the warmer part of the wall.
3. Matches other products from SONIPLASTICS and DECKO DOORS.

OPTIONS

- A. Double or triple glass.
- B. Multitude of interior or exterior mouldings.
- C. Choice of interior and exterior colors.

PERFORMANCES

Primary designator: **Class CW - PG75 - 1500 x 1500 mm (59 x 59 in) - Type FW**

Positive design pressure (DP): 3600 Pa (75.19 psf)

Negative design pressure (DP): -3600 Pa (-75.19 psf)

Water penetration resistance test pressure: 720 Pa (15.04 psf)

Canadian air infiltration / exfiltration level: A3

Results obtained according to standards:

AAMA/WDMA/CSA 101/I.S.2/A440-11 (NAFS 2011), CSA A440S1-09 & CSA A440S1-17

AAMA/WDMA/CSA 101/I.S.2/A440-17 (NAFS 2017), CSA A440S1-19



COMPATIBLE PRODUCTS



DECKODOORS.COM